



Guarantees*

- Lifetime Structural Warranty
- 25 Year Wear Warranty

*Warranty subject to terms and conditions. See www.goldenfield.com.au for details.



Sizes: 1850mm x 125mm x 14mm

Hardness: Janka Rating 15

Finish: Standard semi-gloss German UV acrylic urethane providing extra anti-scratch and abrasion resistance. Coating is water based, solvent free and exceeds the allowable US and European (E1) standards <E1,0.00155ppm for off-gassing.

Moisture Content: Less than 12%

- Eco friendly renewable, recyclable and biodegradable
- Healthy alternative
- Durable bamboo flooring is composed of complex fibres that do not absorb moisture as easily as wood.
 Bamboo has the highest hardness rating from any other floor, it will last a lifetime!
- Natural beauty Green Earth strand woven bamboo flooring boasts a unique appearance that complements all decors. Exotic and elegant, the beauty of Green Earth Bamboo will enhance your interior while remaining true to its natural origins.
- Premium quality looking beautiful forever.

Green Earth bamboo Technical Specifications

The manufacturers of Green Earth's bamboo flooring is a current holder of CE Certificate ISO9001 in Quality Management, and is a ISO14001 Environmental Management certified company. They also use world leading equipment such as HOMAG and BURKLE. Production is undertaken using European licensed click system, and also a European Treffert coating.



Care & Maintenance*

- Do not drag heavy objects across the floor
- High heeled and spiked shoes could cause damage to your floor
- Keep pets nails trimmed and paws clean and free of dirt, gravel, grease, oil and stains
- Do not use oil soaps, liquid or wax products or other household cleaners that contain citrus, lemon, tung oil or ammonia, but reputable floor cleaners

*See www.goldenfield.com.au for details.



Natural



Natural Antique



Carbonized



Carbonized Antique



Autumn



Vintage



Lime Wash



Champagne



Brushed Craftwood



2G Fold Down Locking **Technology**

- Strong and durable locking
- Robust and easy to install
- · Suitable for all floor panel widths
- Vertical and horizontal locking

The strength of the mechanical locking is divided into two different aspects, visual gap opening at 0.2mm and total strength before the lock is broken or the product slides apart.

The Välinge profile is by far the strongest lock with a strength exceeding twice the strength of a competitive lock. By using the Välinge profile you are among the strongest in the business.



Please see www.valinge.se for further details.



Distributor



For more information, please visit our website: www.goldenfield.com.au or email to info@goldenfield.com.au or call 1300 866 800















